



MODELO	ROTOR TIPO	Ø ROTOR	POTÊNCIA (HP)	ROTAÇÃO (RPM)	VAZÃO (m ³ /min)	PRESSÃO (mmCA)	RUIDO (dba)	A	B	C	D	E	F	G	H	I	J	K
SEMAPRO	RAD	190	½	3500	19,6	75	80	182	Ø100	123	122	118	166	Ø100	300	80	Ø150	102
SEMAPRO	SIR	167	½	3500	20,5	82	75	182	Ø100	123	122	118	166	Ø100	300	80	Ø150	102
SAC 1/2 MN	SIR	190	½	1750	16	30	63	172	160	189	139	226	310	140	398	80	Ø150	200
SAC 1/2 MAR	RAD	190	½	3500	17	95	88	150	120	211	151	226	310	110	376	80	Ø150	200
SAC 1/2 TN	SIR	190	½	1750	16	30	63	172	160	189	139	208	310	140	380	80	Ø150	200
SAC 1/2 TAR	RAD	190	½	3500	17	95	88	150	120	211	151	200	310	110	350	80	Ø150	185
SAC 1 MN	SIR	230	½ - 1	1750	22 / 24	38 / 40	63 / 64	220	160	271	211	269	352	160	489	80	Ø160	220
SAC 1 MAR	RAD	230	1	3500	20	120	89	166	130	238	168	269	352	100	435	80	Ø160	220
SAC 1 TN-0,5	SIR	230	½	1750	22	38	63	220	160	271	211	251	352	160	471	80	Ø160	220
SAC 1 TN	SIR	230	1	1750	24	40	64	220	160	271	211	260	352	160	480	80	Ø160	230
SAC 1 TAR	RAD	230	1	3500	20	120	89	166	130	238	168	251	352	100	417	80	Ø160	220
SAC 2 MN	SIR	260	1 - 2	1750	28 / 30	45 / 48	66 / 68	228	180	299	229	309	386	180	537	80	Ø180	240
SAC 2 MAR	RAD	260	2	3500	35	160	92	200	130	285	214	309	386	110	509	80	Ø180	240
SAC 2 TN-1	SIR	260	1	1750	28	45	66	228	180	299	229	300	386	180	528	80	Ø180	240
SAC 2 TN	SIR	260	2	1750	30	48	68	228	180	299	229	310	386	180	537	80	Ø180	240
SAC 2 TAR	RAD	260	2	3500	35	160	92	200	130	285	214	300	386	110	500	80	Ø180	240
SAC 3 MN	SIR	300	1,5 - 3	1750	52 / 55	60 / 65	70 / 77	288	210	336	256	320	440	210	608	80	Ø220	270
SAC 3 MAR	RAD	300	3	3500	45	190	92	237	150	288	219	320	440	150	557	80	Ø220	270
SAC 3 TN-1,5	SIR	300	1,5	1750	52	60	75	288	210	336	256	310	440	210	598	80	Ø220	250
SAC 3 TN	SIR	300	3	1750	55	65	77	288	210	336	256	320	440	210	608	80	Ø220	270
SAC 3 TAR	RAD	300	3	3500	45	190	92	237	150	288	219	320	440	150	557	80	Ø220	270
SAC 4 MN	SIR	330	2	1750	58	83	85	343	230	331	270	350	500	230	693	80	Ø220	270
SAC 4 TN-2	SIR	330	2	1750	58	83	85	343	230	331	270	350	500	230	693	80	Ø220	270
SAC 4 TN	SIR	330	4	1750	60	88	86	343	230	331	270	360	500	230	703	80	Ø220	270
SAC 4 TAR	RAD	330	5	3500	68	250	101	255	160	356	275	360	500	140	615	80	Ø220	270
SAC 5 MN	SIR	360	3	1750	70	90	92	338	250	385	280	350	500	250	688	80	Ø240	270
SAC 5 TN-3	SIR	360	3	1750	70	90	92	338	250	385	280	350	500	250	688	80	Ø240	270
SAC 5 TN	SIR	360	5	1750	75	95	94	338	250	385	280	360	500	250	698	80	Ø240	270
SAC 5 TAR	RAD	360	7,5	3500	100	300	102	272	180	385	280	372	500	160	644	80	Ø240	340

Valores sujeitos a alterações e sem prévio aviso